



block steel surface. Zn - Ni  
Axle steel surface Zn - Ni and polished  
Seal:  
- dynamic O.Ring NBR & Teflon support ring

Operating conditions:  
Medium: Hydraulic oil  
(Dirt particles size up to max. 25 $\mu$ )  
Working pressure: min. 10bar up to max. 350bar  
Temperature: from -30°C to +95°C  
Suitable for rotary and oscillating movements to a sliding speed maximum 0,01m/sec., (but not constant)  
(Rotary speed is dependent on the shaft diameter)

	A	B	C	D	E	VK	SW	Thread 1	pipe connection	Thread 2
GK 1229/00	58,0	37,5	44,0	28,0	12,0	32	24	M18 x 1,5	12L	M18 x 1,5
* GK 1315/00	58,0	37,5	44,0	28,0	12,0	32	24	M20 x 1,5	12S	M18 x 1,5
GK 1316/00	58,0	37,5	44,0	28,0	12,0	32	24	M20 x 1,5	12S	M18 x 1,5
GK 1224/00	58,0	37,5	44,0	28,0	12,0	32	24	M22 x 1,5	15L	M18 x 1,5
GK 1294/00	59,0	38,5	44,0	28,0	12,0	32	27	M22 x 1,5	15L	M22 x 1,5
GK 1355/00	59,0	38,5	46,0	30,0	12,0	32	27	M24 x 1,5	16S	M22 x 1,5
GK 1313/00	59,0	38,5	44,0	28,0	12,0	32	27	M26 x 1,5	18L	M22 x 1,5
GK 1346/00	73,0	48,0	52,0	32,0	14,0	40	32	M26 x 1,5	18L	M22 x 1,5
GK 1337/00	73,0	48,0	56,0	36,0	14,0	40	32	M30 x 2,0	20S	M22 x 1,5
GK 1339/00	75,0	50,0	56,0	36,0	16,0	40	32	M30 x 2,0	20S	M27 x 2,0

\*block with radius

Issue: 08/2015  
Technical changes are reserved to us.